


ANSI B 16.28

КОЛЕНО - КРАТОК РАДИУС
ELBOW - SHORT RADIUS



NPS	DN	OD	A	STANDART WEIGHT			EXTRA STRONG			DOUBLE EXTRA STRONG		
				D	WT T	KG	D	WT T	KG	ID	WT T	KG
1"	25	33,4	25	26,64	3,38	.11	-	-	-	-	-	-
1 1/4"	32	42,2	32	35,05	3,56	.17	-	-	-	-	-	-
1 1/2"	40	48,3	38	40,89	3,68	.23	38,1	5,08	.34	27,94	10,16	68
2"	50	60,3	51	52,5	3,91	.40	49,25	5,54	.68	38,2	11,07	1,26
2 1/2"	65	73	64	62,71	5,16	.79	59	7,01	1,01	44,98	14,02	2,21
3"	80	88,9	76	77,93	5,49	1,35	73,66	7,62	1,69	58,4	15,24	3,15
3 1/2"	90	101,6	89	90,12	5,74	1,8	85,45	8,08	2,48	69,29	16,15	4,73
4"	100	114,3	102	102,26	6,02	2,70	97,18	8,56	3,5	80,06	17,12	6,35
5"	125	141,3	127	128,19	6,55	4,28	122,25	9,53	6,10	103,2	19,05	12,00
6"	150	168,3	152	154,05	7,11	7,00	146,33	10,97	10,1	124,38	21,95	19,4
8"	200	219,1	203	202,72	8,18	14,0	193,68	12,70	21	174,63	22,23	36
10"	250	273,1	254	254,50	9,27	25	247,65	12,70	32	-	-	-
12"	300	323,9	305	304,8	9,53	35	298,45	12,70	45	-	-	-
14"	350	355,6	356	336,6	9,53	47	330,02	12,70	59	-	-	-
16"	400	406,4	406	387,4	9,53	53	381,0	12,70	72	-	-	-
18"	450	457,2	457	438,2	9,53	67	431,8	12,70	87	-	-	-
20"	500	508,0	508	489,0	9,53	95	482,6	12,70	126	-	-	-
24"	600	609,6	610	590,6	9,53	130	584,2	12,70	167	-	-	-

