





EN 1092-1-05

СЛЕПА ПРИРАБНИЦА PN16 BLIND FLANGE PN16



NPS	FLANGE				SCREWS			Form B	Form B
	D	b	k	d _{g max.}	Number	Thread	d ₂	KG	KG
10	90	16	60		4	M 12	14	0,63	
15	95	16	65		4	M 12	14	0,72	
20	105	18	75		4	M 12	14	1,01	
25	115	18	85		4	M 12	14	1,23	
32	140	18	100		4	M 16	18	1,8	
40	150	18	110		4	M 16	18	2,09	
50	165	18	125		4	M 16	18	2,88	
65	185	18	145	55	4	M 16	18	3,66	3,7
80	200	20	160	70	8	M 16	18	4,77	4,83
100	220	20	180	90	8	M 16	18	5,65	5,75
125	250	22	210	115	8	M 16	18	8,42	8,59
150	285	22	240	140	8	M 20	22	10,4	10,6
175	315	24	270	165	8	M 20	22	14	14,3
200	340	24	295	190	12	M 20	22	16,1	16,5
250	405	26	355	235	12	M 24	26	24,9	25,6
300	460	28	410	285	12	M 24	26	35,1	36,1
350	520	30	470	330	16	M 24	26	47,8	49,1
400	580	32	525	380	16	M 27	30	63,5	65,3
500	715	36	650	475	20	M 30	33	102	105

СЛЕПА ПРИРАБНИЦА PN25 BLIND FLANGE PN25



NPS	FLANGE				SCREWS			Form B	Form B
	D	b	k	d _{g max.}	Number	Thread	d ₂	KG	KG
10	90	16	60		4	M 12	14	0,72	
15	95	16	65		4	M 12	14	0,81	
20	105	18	75		4	M 12	14	1,24	
25	115	18	85		4	M 12	14	1,38	
32	140	18	100		4	M 16	18	2,03	
40	150	18	110		4	M 16	18	2,35	
50	165	20	125		4	M 16	18	3,2	
65	185	22	145	55	8	M 16	18	4,29	4,33
80	200	24	160	70	8	M 16	18	5,88	5,94
100	235	24	190	90	8	M 20	22	7,54	7,64
125	270	26	220	115	8	M 24	26	10,80	11,00
150	300	28	250	140	8	M 24	26	14,5	14,7
175	330	28	280	165	12	M 24	26	17,3	17,6
200	360	30	310	190	12	M 24	26	22,3	22,7
250	425	32	370	237	12	M 27	30	33,5	34,5
300	485	34	430	285	16	M 27	30	46,3	47,3
350	555	38	490	332	16	M 30	33	68	69,3
400	620	40	550	380	16	M 33	36	89,7	91,5
500	730	51	660	475	20	M 33	36	138	141